

# **BROCHURE**

# FA-249EX-SS

Zone 1 Stainless Steel LED Marine Lantern 3-10 NM at 0.74T



#### **OVERVIEW**

Zone 1 certified LED marine lantern that is rugged, compact and lightweight, particularly suitable for highly corrosive environments due to a complete 316 Stainless Steel body. Compliant with IALA and DECC recommendations. The FA-249EX is ideal for fixed offshore structures, jetty lights and buoys.

#### **CERTIFICATES**

- ATEX Certificate Number: ITS16ATEX101123X
- IECEx Certificate Number: IECEx ITS 16.0053X
- Coding: Ex II 2 G Ex db op is IIB T5 Tamb -20°C +55°C Gb (-40° optional)

#### **KEY FEATURES**

- · 316L Stainless Steel body
- · Designed to withstand harsh marine environments
- Low power consumption
- · Ability to integrate with wide array of power systems
- · Factory preset flash characteristics to customer specifications
- Ingress Protection: IP-66

## **OPTIONAL FEATURES**

- · Uniflash Series GPS synchronizing system
- Remote monitoring
- · 365 day timer (Astronomical timer)

## **PERFORMANCE FEATURES**

- Range: 3 10 NM
- 255 + 1 special programmable position
- Software programmable:

Photocell

Low voltage disconnect

Special flash rhythm

Specialized current settings

Solar charge control voltage setting

- · 360° visibility
- Vertical Divergence: 20° at 10% and 7° at 50%
- High-efficiency TracSwitcher current controls; 82% of the battery current reaches the LED array on flash; 2mA idle current between flashes

MECHANICAL SPECIFICATIONS	
Height	441mm
Depth	305mm
Weight	8kg
Mounting	4x16mm holes on 200mm PCD (3-Hole pattern also available)
Lens Type	155mm 360° Visibility Acrylic Fresnel Lens
Available Colours	IALA White, Red, Green & Amber
ELECTRICAL SPECIFICATIONS	

# ELECTRICAL SPECIFICATIONS

Input Voltage 6, 12 or 24V DC 120 or 230V AC

Power Consumption 3 - 24W (Range dependent)



